



BLUETOOTH SERIES THERMAL PRINTER




GROWING 100+
SERVICE PARTNERS ACROSS SOUTH INDIA




**Printing Speed
Upto 280 mm/sec**




**Supports Wall
Mounting**



**Multi-Interface
Options**




**Adjustable 2-Inch
& 3-Inch Guide**



**Multi Connect
Printing**



**2 to 3-Inch Mode
Selector**



**Minimal
Space
Design**



**1D & 2D
Barcode
Support**



**Built-in Auto
Cutter for
Precision**

www.shanco.in

Dedicated Helpdesk Team Call - 75 410 410 75

*Terms and Conditions Apply

*Trademark Registered



Three Years
RTB Warranty



100+ Service
Networks

SPECIFICATIONS

MODEL	B80U	B80UN	B80UW
Printing Model	Direct Thermal Printer		
Resolution	203 DPI,8 Dots/mm		
Print Speed	280mm/s		
Interface	Bluetooth + USB + Cash Drawer	Bluetooth + USB+ LAN + Cash Drawer	Bluetooth + USB + WI-FI + Cash Drawer
Auto Cutter	Supports Full Cut Or Half Cut		
Power	Input: 100 - 240V AC, 50-60 HZ		
	Output: 24V DC - 2.5A		
Instruction	ESC/POS Compatible Commands		
Flash	Input: Buffer 64 Bytes		
	NV: Flash 32M Bytes		
Character	ASCII 9x17, 12x24		
Barcode	1D:UPC-A,UPC-E,EAN-8,EAN-13,CODE39,ITF,CODEBAR,CODE128,CODE93		
	2D: QR CODE		
Paper Width	Standard Thermal Printer Paper , Width: 79.5±0.5mm		
Environment	Operating Condition : -10°C ~ 50°C , 25% ~ 80% RH		
	Storage Condition : -40°C ~ 70°C , ≤90% RH (40°C)		
Size	128mm X 170mm X 120mm (w x l x h)		
Weight	1.5 Kg (Approx)		
Software	Windows (WIN7/WIN8/WIN10/WIN11/Vista/XP/2000); Compatability with Android and MAC		