



BLUETOOTH SERIES THERMAL PRINTER




GROWING 100+
SERVICE PARTNERS ACROSS SOUTH INDIA




**Printing Speed
Upto 280 mm/sec**




**Supports Wall
Mounting**



**Multi-Interface
Options**



**Adjustable 2-Inch
& 3-Inch Guide**



**Multi Connect
Printing**



**2 to 3-Inch Mode
Selector**



**Minimal
Space
Design**



**1D & 2D
Barcode
Support**



**Built-in Auto
Cutter for
Precision**

www.shanco.in

Dedicated Helpdesk Team Call - 75 410 410 75

*Terms and Conditions Apply

*Trademark Registered



Three Years
RTB Warranty



100+ Service
Networks

SPECIFICATIONS

MODEL	B80U	B80UN	B80UN-ELITE
Printing Model	Direct Thermal Printer		
Resolution	203 DPI, 8 Dots / mm		
Print Speed	280 mm/s		
Interface	Bluetooth + USB + Cash Drawer	Bluetooth + USB + LAN + Cash Drawer	Bluetooth + USB + Wi-Fi + Cash Drawer
Auto Cutter	Support Full Cut or Half Cut		
Power	Input: 100 - 240V AC, 50 - 60 HZ		
	Output: 24V DC, 2.5 A		
Instruction	ESC / POS Compatible Commands		
Flash	Input: Buffer 64 Bytes		
	NV: Flash 32M Bytes		
Character	ASCII 9x17, 12x24		
Barcode	1D: UPC-A, UPC-E, EAN-8, EAN-13, CODE39, ITF, CODEBAR, CODE128, CODE93		
	2D: QR CODE		
Paper Width	Standard Thermal Printer Paper, Width: 79.5 ± 0.5 mm		
Environment	Operating Condition: -10°C~50°C, 25%~80%RH		
	Storage Condition: -40°C~70°C, ≤90% RH (40° C)		
Size	128 mm x 170 mm x 120 mm (w x l x h)		
Weight	1.5 Kgs (Approx.)		
OS Support	Windows 7/8/10/11/Vista/XP/2000 ; Compatability with MAC and Android		